



Slats

for Chain-Link Fence



Eastern Hedge

Eastern Hedge creates a natural hedge look on chain link fence, which requires no maintenance, water or trimming.

Design: Core is made with 16-gauge braided galvanized wire. The "needles" are made with 3-mil PVC.

Installation: Requires no locking device or tools. Eastern Hedge installs much like our classic Bottom-Locking or Top-Locking slats.

Standard Heights: 4ft., 5ft., 6ft., 8ft.

Fence Size: For most mesh sizes. Not intended for use with mini-mesh wire.

Coverage: 10 linear feet per box.

UV stabilized to protect against the harmful rays of the Sun.

Flame retardant.

10 Year pro rated warranty.



BP6-WT

Top Locking Slats

This slat provides an economical and attractive way to enhance any chain link fence. The locking system is located near the top of the slats to ensure a clean, straight edge along the top of the fence.

Design: Top-Locking Slats are flat and tubular in shape, with circular notched holes located near the top of the slat.

Fast & Easy Installation: Simply insert the slats vertically from the top to bottom, keeping the locking holes on top. Then thread the flexible locking channel horizontally through the notched holes in the slats.

These holes are elliptical to ensure they always stay open for fast and easy threading.


Standard Heights: 4ft., 5ft., 6ft., 8ft.

Slat Length: 2" shorter than the overall height of the fence.

Flexible, Top Locking Channel: Also available on a continuous 200 ft. reel for larger jobs.

Wind Load and Privacy Factor: Approximately 75%.

Slat Name	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag Covers 10 linear feet Covers 10 linear feet	
Top Lock 2"	1 3/32"	2"	9 or 11		
Top Lock 2 1/4"	1 1/4"	2 1/4"	11 1/2 or 12		
Top 1 3/4"	1" 1"	1 3/4" 2"	11 6	Covers 10 linear feet	



BTP6-WT

Winged Slat

When you need increased privacy, Winged Slats are the answer. With the proven quality and durability of our standard slats plus unique "wings" for extra screening and security, these slats are self locking - no channels are needed!

Unique Patented Design: Includes a rigid, flat tubular body, with "legs" inside for extra support. Flexible and resilient wing portions are positioned on each side of the slat body. Serrations are added to the wings for easier installation and locking power.

Installation: Insert the slats vertically into the fence, from top to bottom, no tool is necessary. That's it! The serrated wings grip the knuckles of the wire mesh, securing the slat in the fence.

Standard Heights: 4ft., 5ft., 6ft., 8ft.

For heights exceeding 7ft., we recommend using two half sizes (i.e. for 10ft. fence use two 5ft. slats.) This will help during installation.

Slat Length: 2" shorter than the overall height of the fence.

Wind Load and Privacy Factor: Approximately 90%.

Slat Name	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag	
Winged Slat	1 7/16"	2" mesh only	9 gauge only	Covers 10 linear feet	

Fence Product Specifications

MATERIALS

(HDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the Sun and lengthen the life of the product. The only exceptions are:

 Winged Slats which also include Ethyl Vinyl Acetate (EVA), which is a softer plastic to keep wings flexible and resilient.

To properly order the product you are looking for, you must first put the product ID, followed by the height, a dash, and the color. For example: BP6-WT is Top Locking Slat that is 6ft. high and white.

The product codes are: BP (Top Locking Slat) • BTP (Winged Slat) • and EH (Eastern Hedge). The color codes are:

DS - Desert Sand • EG - Eastern Green • WT - White • BR - Brown
• BK - Black • RD - Redwood • GY - Grey.

Other colors and heights are available.

HDPE TECHNICAL PROPERTIES

Property	<i>l</i> a	llu	е	
----------	------------	-----	---	--

Melt Index (.6) A low melt index indicates improved stress and crack resistance.

Density (.957) Polythylene ranges anywhere from .914 to .960 in density.

A higher density yields maximim stiffness without becoming overly brittle.

Minimum Temp. (-76°F) Polythylene stays flexible even at this temperature extreme.

Maximum Temp. (250°F) Polythylene does not distort until reaching this temperature.

Tensile Strength (3,700 psi) Material will not suffer distortion at lesser loads or impacts.

Property Value

 Specific Gravity
 1.45 +/- .02

 Minimum Temp.
 0°F

 Maximum Temp.
 160°F

 Tensile Strength
 6,200psi

Flexural Strength 12,000psi
Impact Strength 4.0 ft-lb/inch @ 23°C (73°F)

DURABILITY

Fence Products are resistant to: severe weather conditions, salt water, sand, road dirt most acids, alchohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

MAINTENANCE

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

COLOR DISCLAIMER

Due to limitations and variations in the printing process, the color charts shown are only approximations of the actual fence product material color. Sample color swatch kits are available from your authorized Fence Products distributor and their dealers.

Slat Colors



Gray

Brown

Desert Sand

Redwood

Black

White

(colors are approximations)



PHONE: 800-339-3362 • www.easternfence.com

Gastern!

SUPPLIERS TO THE TRADE ONLY

EH&PS 0916 | Eastern Fence @2016. All Rights Reserved.